

< Back to bandsaw machines

KASTO^{ssb} A 2



Q Zoom



KASTO^{ssb} A 2

Fully hydraulic and automatic high-performance bandsawing machine of robust construction, with saw blade moving parallel in vertical direction, for cutting of profiles, tubes and solid material of all qualities, including difficult to cut material (e.g. titanium, Hastelloy, Inconel).

- Totally enclosed installation provides high safety and excellent noise damping
- Sturdy clamping vice system permits high cutting accuracy and reliable clamping of the workpiece
- Vertically cutting saw blade optimizes chip flow
- Blade exchange is easy and virtually maintenance free
- Minor coolant loss and easy cleaning



Download brochure (PDF 2.6 MB)

We are happy to help:



Hotline Sales

Vertrieb, Hotline

Phone: +49 7841 61-100

kasto@kasto.com

[Make an inquiry](#)



Technical data
KASTOssb A 2

Cutting range	
Cutting range	260x 260 mm / 260 mm
Cutting range bundle width	150 - 260 mm
Cutting range bundle height	0 - 200 mm
Clamping range	0 - 260 mm
Smallest size to be cut	Ø 10 mm
Shortest length of cut-off piece	5 mm
Minimal remnant length, automatic Operation	110mm
Minimal remnant length, single cut	10mm

Dimensions and weights	
Length	1.670 mm
Width	2.080 mm
Height	2.130 mm
Material support height	950 mm
Total weight	2200 kg

Performance characteristics	
Total connected load	9.5 kW
Power of saw motor	5.5 kW
Cutting speed infinitely variable	15 - 125 m/min
Automatic feed length, single stroke	600 mm
Multiple feed length	9999 mm
Clamping force of machine vice	1100 - 6800 N
Clamping force of feed vice	1100 - 6800 N
Dimensions of saw blade	4115 x 41 x 1.3 mm

We reserve the right to make technical changes.

Download data sheet

Recommend



Please contact consultant



Services & Support options



Assistance Packages




KASTOretrofit




Repairs



24/7 Hotline



KASTO [RemoteAssistance]



Spare parts



Inspections and maintenance