


< Back to bandsaw machines

KASTOmicut E 4.6



Q Zoom





KASTOmicut E 4.6

Manual swivelling frame bandsaw

Die KASTOmicut E 4.6 saws round material up to 335 mm diameter and flat material with dimensions up to 460 x 335 mm. It is specially designed for single-sided mitre angles and is suitable for cuts from 0 to +60 degrees. The saw has a hydraulically controlled feed. Blade and material tensioning is carried out mechanically. The cutting speed can be continuously adjusted between 20 and 110 metres per minute. This opens up a wide range of possibilities for the user with different material qualities.

Characteristics:

- Frequency-controlled infinitely saw drive
- Fully hydraulic saw feed control
- Linear-guided overrunning clamping device
- Infinitely adjustable mitre angle (90° to +60°)
- Infinitely variable saw blade arm adjustment



Download brochure (PDF 3.0 MB)

We are happy to help:



Hotline Sales

Vertrieb, Hotline

Phone: +49 7841 61-100

kasto@kasto.com

[Make an inquiry >](#)

Technical data

KASTOmicut E 4.6

Cutting range	
Form	
90°	160 / 160 x 160 / 335 / 460 x 335 / 335 x 335 mm
+ 45°	- / - / - / 320 / 250 x 335 / 300 x 300 mm
+ 60°	- / - / - / 210 / 180 x 335 / 200 x 200 mm
Remnant length single cut	30 mm

Mass and height	
Length x width x height	800 x 2.350 x 2.000 mm
Material support height	700 mm

Performance characteristics	
Total power	2,0 kW
Drive Power	1,5 kW
Cutting speed	20 - 110 m/min
Dimensions of saw blade	3.830 x 27 x 0,9 mm

We reserve the right to make technical changes.

[Download data sheet](#)

[Recommend](#)



[Please contact consultant](#)

